

HVR 16 analog + 8 IP channel 2HDD

Technical Specifications

Perimeter Protection	
Performance	2 channels, 10 IVS for each channel
Object Classification	Human/Vehicle secondary recognition for tripwire and intrusion
AI Search	Search by target classification (Human, Vehicle)
Storage	
Internal HDD	2 SATA Ports, up to 10TB capacity for each disk
eSATA	N/A
Auxiliary Interface	
USB	2 USB Ports (1 USB 2.0 , 1 USB 3.0)
RS485	1 Port, for PTZ Control
SMD Plus	
Performance	16 channels
AI Search	Search by target classification (Human, Vehicle)
Video and Audio	
Analog Camera Input	16 channels, BNC
HDCVI Camera Input	5MP, 4MP, 1080P@25/30fps, 720P@50/60fps, 720P@25/30fps
AHD Camera Input	5MP, 4MP, 3MP, 1080P@25/30, 720P@25/30fps
TVI Camera Input	5MP, 4MP, 3MP, 1080P@25/30, 720P@25/30fps
CVBS Camera Input	PAL/NTSC
IP Camera Input	16+8 channels, each channel up to 6MP
Audio In/Out	1/1, RCA
Two-way Talk	Reuse audio in/out, RCA
Recording	
Compression	AI Coding/H.265+/H.265/H.264+/H.264
Resolution	5M-N, 4M-N, 1080P, 1080N, 720P, 960H, D1, CIF
Record Rate	Main stream: All channel 5M-N (1fps-10fps); 4M-N/1080P (1fps-15fps); 1080N/720P/960H/D1/CIF (1fps-25/30fps) Sub stream: D1/CIF (1fps-15fps)
Bit Rate	32 Kbps-6144 Kbps Per Channel
Record Mode	Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Record Interval	1 – 60 min (default: 60 min), Pre-record: 1 s-30 s, Post-record: 10 s-300 s
Audio Compression	AAC (only for the 1st channel), G.711A, G.711U, PCM
Audio Sample Rate	8 KHz, 16 bit Per Channel
Audio Bit Rate	64 Kbps Per Channel
Display	
Interface	1 HDMI ,1 VGA
Resolution	VGA: 1920 × 1080, 1280 × 1024, 1280 × 720 HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720 It changes to 1920 × 1080, 1280 × 1024, 1280 × 720 when Face or IVS & SMD is selected in AI Mode.
Multi-screen Display	When IP extension mode not enabled: 1/4/8/9/16 When IP extension mode enabled: 1/4/8/9/16/25
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording